POINTE DE CAUX
CHEMICAL TANKER



PRINCIPAL DIMENSIONS

Length Overall	:	110.00 m
Beam	:	14.00 m
Draught (Scantling)	:	4.80 m
Depth	:	6.05 m

DEADWEIGHT AND TONNAGE

DWT (at Design)	:	4700 t
GRT/NT	:	3020/1540 t

CAPACITIES

Cargo Capacity	:	5614 m³ (100%)
Water Ballast	:	2687 m³
MGO	:	92 m³
Fresh Water	:	124 m³
Design Speed	:	10 knots

CARGO EQUIPMENT

Pumps	:	FRAMO
Type	:	SD125
Capacity	:	10 x 150 cbm/h
Cargo Crane	:	SQL 2t @18.00 m

BOW THRUSTER

Manufacturer	:	Schottel
Type	:	STT 1 FP
Speed	:	400 kW @1470 rpm

DIESEL ELECTRIC PROPULSION SYSTEM

DIESEL GENERATORS

Design	:	Four (4) Stroke, High Speed
Manufacturer	:	LIAG/MAN
Output	:	3 x 565 kWe @1500 rpm

PROPULSION PLANT

Manufacturer	:	Schottel
Type	:	SRE 270 SCHOTTEL EcoPeller
Speed	:	650 kW @1200 rpm

BATTERY SYSTEM

Manufacturer	:	SAFT
Type	:	Seanergy 41MFe - 750V
Capacity	:	314 kwh

CLASS

BV I ✣ HULL ✣ MACH, Oil Tanker – Chemical Tanker - ESP - (IMO Type 2), UNRESTRICTED NAVIGATION, ✣ AUT-UMS, ✣ AUT-PORT, ✣ AVM-APS, ✣ SYS-NEQ-1, ✣ SYS-COM, VCS, IG, ERS-S, CPS(WBT), CLEANSHIP, GREENPASSPORT EU, INWATERSURVEY, MONSHAFT, ✣ Veristar-HULL, ELECTRIC HYBRID (PM, PB)